# Heavy duty wheel 200 mm, polyamide, plain bearing, axle hole 25 mm, 500 kg, product code 23706, wheel centre white

Heavy duty wheel with a 200 mm wheel, solid polyamide wheel, on plain bearing. It carries 500 kg dynamic and 620 kg static, with a 25 mm axle hole.



Drawing number **2-734** | Product code **23706** | EAN **3838461237065**

| | |
|---|---|
| **Type** | Heavy duty wheel |
| **Wheel diameter** | 200 mm |
| **Wheel width** | 44 mm |
| **Tread** | solid polyamide wheel, 70±5 Shore D |
| **Wheel centre** | polyamide |
| **Bearing** | plain bearing |
| **Load capacity, dynamic** | 500 kg |
| **Load capacity, static** | 620 kg |
| **Axle hole** | 25 mm |
| **Weight** | 0.8 kg |
| **Temperature, continuous** | -25 to +80 °C |
| **Temperature, short exposure (max. 10 min)** | -30 to +110 °C |
| **Fitting** | Wheel hub |
| **Hub length** | 59 mm |
| **Tread hardness** | 70 Shore D |

## Properties and use

Low wear, little effort to keep rolling and easy to turn. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.