Wheel 150 mm, black rubber, roller bearing, axle hole 20 mm, 170 kg, product code 30245

Wheel with black rubber tread, wheel diameter 150 mm, on roller bearing. It carries 170 kg dynamic and 210 kg static, with a 20 mm axle hole.



Drawing number **2-945 A** | Product code **30245** | EAN **3838461302459**

Type	Wheel
Wheel diameter	150 mm
Wheel width	40 mm
Tread	black rubber tread, 80 Shore A
Tread colour	black
Wheel centre	polypropylene
Bearing	roller bearing
Load capacity, dynamic	170 kg
Load capacity, static	210 kg
Axle hole	20 mm
Weight	0.65 kg
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C
Fitting	Wheel hub
Hub length	58 mm

Tread free of PAH (EU directive 2005/69/EC). Tested to EN 12532.

Properties and use

Suited to wet floors and low obstacles. The rubber tyre damps vibration and noise. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.