Wheel 180 mm, black rubber, roller bearing, axle hole 20 mm, 200 kg, product code 30264

Wheel with a 180 mm wheel, black rubber tread, on roller bearing. It carries 200 kg dynamic and 250 kg static, with a 20 mm axle hole.



Drawing number **2-946 A** | Product code **30264** | EAN **3838461302640**

Type	Wheel
Wheel diameter	180 mm
Wheel width	50 mm
Tread	black rubber tread, 80 Shore A
Tread colour	black
Wheel centre	polypropylene
Bearing	roller bearing
Load capacity, dynamic	200 kg
Load capacity, static	250 kg
Axle hole	20 mm
Weight	1.2 kg
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C
Fitting	Wheel hub
Hub length	58 mm

Tread free of PAH (EU directive 2005/69/EC). Tested to EN 12532.

Properties and use

Suited to wet floors and low obstacles. The rubber tyre damps vibration and noise. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.