
Fixed castor 200 mm, pneumatic tyre, roller bearing, plate 135x110 mm, 60 kg, product code 32693

Fixed castor with grey pneumatic tyre, wheel diameter 200 mm, on roller bearing. It carries 60 kg dynamic and 70 kg static, mounted on a 135x110 mm top plate with hole distance 105x80 mm.





Drawing number **2-447 ISO** | Product code **32693** | EAN **3838461326936**

Type	Fixed castor
Wheel diameter	200 mm
Wheel width	50 mm
Tread	grey pneumatic tyre
Wheel centre	polypropylene
Bearing	roller bearing
Load capacity, dynamic	60 kg
Load capacity, static	70 kg
Top plate	135x110 mm
Hole distance	105x80 mm
Fixing hole diameter	11 mm
Overall height	232 mm
Weight	1.32 kg
Temperature, continuous	-5 to +60 °C
Temperature, short exposure (max. 10 min)	-5 to +60 °C

Fork zinc electroplated and Cr(VI)-free. Tread free of PAH (EU directive 2005/69/EC).

Properties and use

Leaves no marks on the floor. Suited to uneven ground, and the pneumatic tyre cushions shocks. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.