Wheel 200 mm, polyamide, plain bearing, axle hole 20 mm, 450 kg, product code 32884, wheel centre white

Wheel, 200 mm wheel diameter, solid polyamide wheel, running on plain bearing. Rated load is 450 kg dynamic, 560 kg static, with a 20 mm axle hole.



Drawing number **2-764 A** | Product code **32884** | EAN **3838461328848**

Type	Wheel
Wheel diameter	200 mm
Wheel width	40 mm
Tread	solid polyamide wheel, 70±5 Shore D
Wheel centre	polyamide
Bearing	plain bearing
Load capacity, dynamic	450 kg
Load capacity, static	560 kg
Axle hole	20 mm
Weight	0.51 kg
Temperature, continuous	-25 to +80 °C
Temperature, short exposure (max. 10 min)	-30 to +110 °C
Fitting	Wheel hub
Hub length	50 mm
Tread hardness	70 Shore D

Properties and use

Polyamide resists many chemicals, carries high loads and takes shock impact. It tolerates large temperature swings. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.