Swivel transport castor with total lock 160 mm, black rubber, plain bearing, bolt hole 12.5 mm, 180 kg, product code 34094

Swivel transport castor with total lock with black rubber tread, wheel diameter 160 mm, on plain bearing. It carries 180 kg dynamic and 220 kg static, fixed with a 12.5 mm bolt hole. The total lock brakes the rotation of the wheel and the swivel head.





Drawing number **2-681 L12** | Product code **34094** | EAN **3838461340949**

Type	Swivel transport castor with total lock
Wheel diameter	160 mm
Wheel width	40 mm
Tread	black rubber tread, 80 Shore A
Tread colour	black
Wheel centre	steel, zinc electroplated, Cr(VI)-free
Bearing	plain bearing
Load capacity, dynamic	180 kg
Load capacity, static	220 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	190 mm
Offset	50 mm
Brake	total lock (locks wheel and swivel)
Weight	2.35 kg
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C
Top plate size	93 mm

Fork zinc electroplated and Cr(VI)-free. Tread free of PAH (EU directive 2005/69/EC). Tested to EN 12532.

Properties and use

Steers easily and copes with uneven floors and obstacles. Steel rim and rubber tyre make a strong wheel. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.