Swivel transport castor with total lock 180 mm, black rubber, roller bearing, bolt hole 12.5 mm, 200 kg, product code 34095

Swivel transport castor with total lock with a 180 mm wheel, black rubber tread, on roller bearing. It carries 200 kg dynamic and 250 kg static, fixed with a 12.5 mm bolt hole. The total lock brakes the rotation of the wheel and the swivel head.





Drawing number **2-207 L12** | Product code **34095** | EAN **3838461340956**

Type	Swivel transport castor with total lock
Wheel diameter	180 mm
Wheel width	50 mm
Tread	black rubber tread, 80 Shore A
Tread colour	black
Wheel centre	steel, zinc electroplated, Cr(VI)-free
Bearing	roller bearing
Load capacity, dynamic	200 kg
Load capacity, static	250 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	210 mm
Offset	55 mm
Brake	total lock (locks wheel and swivel)
Weight	3.3 kg
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C
Top plate size	93 mm

Fork zinc electroplated and Cr(VI)-free. Tread free of PAH (EU directive 2005/69/EC). Tested to EN 12532.

Properties and use

Steers easily and copes with uneven floors and obstacles. Steel rim and rubber tyre make a strong wheel. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.