
Swivel transport castor 100 mm, black rubber, plain bearing, bolt hole 12.5 mm, 80 kg, product code 34135

Swivel transport castor, 100 mm wheel diameter, black rubber tread, running on plain bearing. Rated load is 80 kg dynamic, 100 kg static, fixed with a 12.5 mm bolt hole.





Drawing number **2-973 L12** | Product code **34135** | EAN **3838461341359**

Type	Swivel transport castor
Wheel diameter	100 mm
Wheel width	32 mm
Tread	black rubber tread, 80 Shore A
Tread colour	black
Wheel centre	polypropylene
Bearing	plain bearing
Load capacity, dynamic	80 kg
Load capacity, static	100 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	128 mm
Offset	40 mm
Weight	0.9 kg
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C
Top plate size	70 mm

Fork zinc electroplated and Cr(VI)-free. Tread free of PAH (EU directive 2005/69/EC). Tested to EN 12532.

Properties and use

Suited to wet floors and low obstacles. The rubber tyre damps vibration and noise. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.