Swivel transport castor with total lock 200 mm, black rubber, plain bearing, bolt hole 12.5 mm, 230 kg, product code 34245

Swivel transport castor with total lock with a 200 mm wheel, black rubber tread, on plain bearing. It carries 230 kg dynamic and 280 kg static, fixed with a 12.5 mm bolt hole. The total lock brakes the rotation of the wheel and the swivel head.





Drawing number **2-992 L12** | Product code **34245** | EAN **3838461342455**

Type	Swivel transport castor with total lock
Wheel diameter	200 mm
Wheel width	50 mm
Tread	black rubber tread, 80 Shore A
Tread colour	black
Wheel centre	polypropylene
Bearing	plain bearing
Load capacity, dynamic	230 kg
Load capacity, static	280 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	232 mm
Offset	60 mm
Brake	total lock (locks wheel and swivel)
Weight	3.15 kg
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C
Top plate size	93 mm

Fork zinc electroplated and Cr(VI)-free. Tread free of PAH (EU directive 2005/69/EC). Tested to EN 12532.

Properties and use

Suited to wet floors and low obstacles. The rubber tyre damps vibration and noise. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.