
Swivel castor 150 mm, polypropylene, plain bearing, bolt hole 12.5 mm, 250 kg, product code 34354, wheel centre white

Swivel castor, 150 mm wheel diameter, solid polypropylene wheel, running on plain bearing. Rated load is 250 kg dynamic, 310 kg static, fixed with a 12.5 mm bolt hole.





Drawing number **2-768 L12** | Product code **34354** | EAN **3838461343544**

Type	Swivel castor
Wheel diameter	150 mm
Wheel width	46 mm
Tread	solid polypropylene wheel, 60±5 Shore D
Wheel centre	polypropylene
Bearing	plain bearing
Load capacity, dynamic	250 kg
Load capacity, static	310 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	180 mm
Offset	50 mm
Weight	1.6 kg
Temperature, continuous	-20 to +60 °C
Top plate size	93 mm
Tread hardness	60 Shore D

Fork zinc electroplated and Cr(VI)-free.

Properties and use

Polypropylene resists acids, wears slowly and rolls with low resistance. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.