
Swivel castor 150 mm, polyamide, roller bearing, bolt hole 12.5 mm, 300 kg, Art. 2-758 L12, wheel centre black

Swivel castor with solid polyamide wheel, wheel diameter 150 mm, on roller bearing. It carries 300 kg dynamic and 370 kg static, fixed with a 12.5 mm bolt hole.





Drawing number **2-758 L12** | SKU **34415** | EAN **3838461344152**

Type	Swivel castor
Wheel diameter	150 mm
Wheel width	46 mm
Tread	solid polyamide wheel, 70±5 Shore D
Wheel centre	polyamide
Bearing	roller bearing
Load capacity, dynamic	300 kg
Load capacity, static	370 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	180 mm
Offset	50 mm
Weight	1.7 kg
Temperature, continuous	-25 to +80 °C
Temperature, short exposure (max. 10 min)	-30 to +110 °C
Top plate size	93 mm
Tread hardness	70 Shore D

Fork zinc electroplated and Cr(VI)-free.

Properties and use

Polyamide resists many chemicals, carries high loads and takes shock impact. It tolerates large temperature swings. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.