
# Swivel castor 100 mm, polyamide, roller bearing, bolt hole 12.5 mm, 200 kg, product code 34463, wheel centre white

Swivel castor with solid polyamide wheel, wheel diameter 100 mm, on roller bearing. It carries 200 kg dynamic and 250 kg static, fixed with a 12.5 mm bolt hole.






Drawing number **2-756 L12** | Product code **34463** | EAN **3838461344633**

| | |
|---|---|
| **Type** | Swivel castor |
| **Wheel diameter** | 100 mm |
| **Wheel width** | 35 mm |
| **Tread** | solid polyamide wheel, 70±5 Shore D |
| **Wheel centre** | polyamide |
| **Bearing** | roller bearing |
| **Load capacity, dynamic** | 200 kg |
| **Load capacity, static** | 250 kg |
| **Fitting** | single bolt hole |
| **Hole diameter** | 12.5 mm |
| **Overall height** | 128 mm |
| **Offset** | 40 mm |
| **Weight** | 0.65 kg |
| **Temperature, continuous** | -25 to +80 °C |
| **Temperature, short exposure (max. 10 min)** | -30 to +110 °C |
| **Top plate size** | 70 mm |
| **Tread hardness** | 70 Shore D |

Fork zinc electroplated and Cr(VI)-free.

## Properties and use

Polyamide resists many chemicals, carries high loads and takes shock impact. It tolerates large temperature swings. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.