
# Swivel castor 150 mm, polyamide, plain bearing, bolt hole 12.5 mm, 300 kg, Art. 2-768 L12, wheel centre white

Swivel castor, 150 mm wheel diameter, solid polyamide wheel, running on plain bearing. Rated load is 300 kg dynamic, 370 kg static, fixed with a 12.5 mm bolt hole.






Drawing number **2-768 L12** | SKU **34483** | EAN **3838461344831**

| | |
|---|---|
| **Type** | Swivel castor |
| **Wheel diameter** | 150 mm |
| **Wheel width** | 46 mm |
| **Tread** | solid polyamide wheel, 70±5 Shore D |
| **Wheel centre** | polyamide |
| **Bearing** | plain bearing |
| **Load capacity, dynamic** | 300 kg |
| **Load capacity, static** | 370 kg |
| **Fitting** | single bolt hole |
| **Hole diameter** | 12.5 mm |
| **Overall height** | 180 mm |
| **Offset** | 50 mm |
| **Weight** | 1.6 kg |
| **Temperature, continuous** | -25 to +80 °C |
| **Temperature, short exposure (max. 10 min)** | -30 to +110 °C |
| **Top plate size** | 93 mm |
| **Tread hardness** | 70 Shore D |

Fork zinc electroplated and Cr(VI)-free.

## Properties and use

Polyamide resists many chemicals, carries high loads and takes shock impact. It tolerates large temperature swings. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.