
Swivel castor with total lock 150 mm, polypropylene, roller bearing, bolt hole 12.5 mm, 250 kg, product code 34553, wheel centre black

Swivel castor with total lock with solid polypropylene wheel, wheel diameter 150 mm, on roller bearing. It carries 250 kg dynamic and 310 kg static, fixed with a 12.5 mm bolt hole. The total lock brakes the rotation of the wheel and the swivel head.





Drawing number **2-791 L12** | Product code **34553** | EAN **3838461345531**

Type	Swivel castor with total lock
Wheel diameter	150 mm
Wheel width	46 mm
Tread	solid polypropylene wheel, 60±5 Shore D
Wheel centre	polypropylene
Bearing	roller bearing
Load capacity, dynamic	250 kg
Load capacity, static	310 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	180 mm
Offset	50 mm
Brake	total lock (locks wheel and swivel)
Weight	1.7 kg
Temperature, continuous	-20 to +60 °C
Top plate size	93 mm
Tread hardness	60 Shore D

Fork zinc electroplated and Cr(VI)-free.

Properties and use

Polypropylene resists acids, wears slowly and rolls with low resistance. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.