Wheel 100 mm, elastic rubber, roller bearing, axle hole 12 mm, 150 kg, product code 39843

Wheel with a 100 mm wheel, elastic rubber tyre, on roller bearing. It carries 150 kg dynamic and 180 kg static, with a 12 mm axle hole.



Drawing number **2-040-20V** | Product code **39843** | EAN **3838461398438**

Type	Wheel
Wheel diameter	100 mm
Wheel width	35 mm
Tread	elastic rubber tyre, 70 Shore A
Tread colour	green
Wheel centre	polyamide
Bearing	roller bearing
Load capacity, dynamic	150 kg
Load capacity, static	180 kg
Axle hole	12 mm
Weight	0.27 kg
Temperature, continuous	-25 to +80 °C
Temperature, short exposure (max. 10 min)	-30 to +110 °C
Fitting	Wheel hub
Hub length	44 mm

Tread free of PAH (EU directive 2005/69/EC).

Properties and use

The elastic rubber tyre starts rolling with little force and rides smoothly. It is gentle on the floor, also when the unit stands still. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.