Wheel 160 mm, elastic rubber, roller bearing, axle hole 20 mm, 350 kg, product code 40124

Wheel with elastic rubber tyre, wheel diameter 160 mm, on roller bearing. It carries 350 kg dynamic and 430 kg static, with a 20 mm axle hole.



Drawing number **2-040-32V** | Product code **40124** | EAN **3838461401244**

Type	Wheel
Wheel diameter	160 mm
Wheel width	50 mm
Tread	elastic rubber tyre, 70 Shore A
Tread colour	green
Wheel centre	polyamide
Bearing	roller bearing
Load capacity, dynamic	350 kg
Load capacity, static	430 kg
Axle hole	20 mm
Weight	0.6 kg
Temperature, continuous	-25 to +80 °C
Temperature, short exposure (max. 10 min)	-30 to +110 °C
Fitting	Wheel hub
Hub length	58 mm

Tread free of PAH (EU directive 2005/69/EC).

Properties and use

The elastic rubber tyre starts rolling with little force and rides smoothly. It is gentle on the floor, also when the unit stands still. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.