
Swivel castor 125 mm, elastic rubber, plain bearing, bolt hole 12.5 mm, 200 kg, product code 40214

Swivel castor with elastic rubber tyre, wheel diameter 125 mm, on plain bearing. It carries 200 kg dynamic and 250 kg static, fixed with a 12.5 mm bolt hole.





Drawing number **2-044-25D** | Product code **40214** | EAN **3838461402142**

Type	Swivel castor
Wheel diameter	125 mm
Wheel width	35 mm
Tread	elastic rubber tyre, 70 Shore A
Tread colour	green
Wheel centre	polyamide
Bearing	plain bearing
Load capacity, dynamic	200 kg
Load capacity, static	250 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	155 mm
Offset	40 mm
Weight	0.95 kg
Temperature, continuous	-25 to +80 °C
Temperature, short exposure (max. 10 min)	-30 to +110 °C
Top plate size	70 mm

Fork zinc electroplated and Cr(VI)-free. Tread free of PAH (EU directive 2005/69/EC).

Properties and use

The elastic rubber tyre starts rolling with little force and rides smoothly. It is gentle on the floor, also when the unit stands still. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.