
# Swivel castor with total lock 200 mm, polyurethane, roller bearing, bolt hole 12.5 mm, 300 kg, product code 40645

Swivel castor with total lock, 200 mm wheel diameter, polyurethane tread, running on roller bearing. Rated load is 300 kg dynamic, 370 kg static, fixed with a 12.5 mm bolt hole. The total lock brakes the rotation of the wheel and the swivel head.






Drawing number **2-055-40V** | Product code **40645** | EAN **3838461406454**

| | |
|---|---|
| **Type** | Swivel castor with total lock |
| **Wheel diameter** | 200 mm |
| **Wheel width** | 50 mm |
| **Tread** | polyurethane tread, 92 Shore A |
| **Tread colour** | green |
| **Wheel centre** | polyamide |
| **Bearing** | roller bearing |
| **Load capacity, dynamic** | 300 kg |
| **Load capacity, static** | 370 kg |
| **Fitting** | single bolt hole |
| **Hole diameter** | 12.5 mm |
| **Overall height** | 232 mm |
| **Offset** | 60 mm |
| **Brake** | total lock (locks wheel and swivel) |
| **Weight** | 3.17 kg |
| **Temperature, continuous** | -20 to +80 °C |
| **Temperature, short exposure (max. 10 min)** | -40 to +100 °C |
| **Top plate size** | 93 mm |
| **Tread material** | Injection-moulded polyurethane |

Fork zinc electroplated and Cr(VI)-free.

## Properties and use

The polyurethane tread resists cuts and suits stony floors. It tolerates large temperature differences. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.