
Swivel castor with total brake 200 mm, polyurethane, ball bearing, bolt hole 12.5 mm, 300 kg, Art. 2-055-40K

Swivel castor with total brake with a 200 mm wheel, polyurethane tread, on ball bearing. It carries 300 kg dynamic and 370 kg static, fixed with a 12.5 mm bolt hole.





Drawing number **2-055-40K** | SKU **40653** | EAN **3838461406539**

Type	Swivel castor with total brake
Wheel diameter	200 mm
Wheel width	50 mm
Tread	polyurethane tread, 92 Shore A
Tread colour	green
Wheel centre	polyamide
Bearing	ball bearing
Load capacity, dynamic	300 kg
Load capacity, static	370 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	232 mm
Offset	60 mm
Brake	total brake (locks wheel and swivel)
Weight	3.33 kg
Temperature, continuous	-20 to +80 °C
Temperature, short exposure (max. 10 min)	-40 to +100 °C
Top plate size	93 mm
Tread material	Injection-moulded polyurethane

Fork zinc electroplated and Cr(VI)-free.

Properties and use

The polyurethane tread resists cuts and suits stony floors. It tolerates large temperature differences. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.