Swivel castor 80 mm, polyamide, roller bearing, bolt hole 12.5 mm, 150 kg, product code 40885

Swivel castor, 80 mm wheel diameter, solid polyamide wheel, running on roller bearing. Rated load is 150 kg dynamic, 180 kg static, fixed with a 12.5 mm bolt hole.



Drawing number **2-064-16V** | Product code **40885** | EAN **3838461408854**

Type	Swivel castor
Wheel diameter	80 mm
Wheel width	35 mm
Tread	solid polyamide wheel, 70±5 Shore D
Wheel centre	polyamide
Bearing	roller bearing
Load capacity, dynamic	150 kg
Load capacity, static	180 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	106 mm
Offset	34 mm
Weight	0.87 kg
Temperature, continuous	-25 to +80 °C
Temperature, short exposure (max. 10 min)	-30 to +110 °C
Top plate size	70 mm
Tread hardness	70 Shore D

Fork zinc electroplated and Cr(VI)-free.

Properties and use

Low wear, little effort to keep rolling and easy to turn. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.