Swivel castor with total lock 100 mm, polyamide, roller bearing, bolt hole 12.5 mm, 200 kg, product code 40943

Swivel castor with total lock with solid polyamide wheel, wheel diameter 100 mm, on roller bearing. It carries 200 kg dynamic and 250 kg static, fixed with a 12.5 mm bolt hole. The total lock brakes the rotation of the wheel and the swivel head.



Drawing number **2-065-20V** | Product code **40943** | EAN **3838461409431**

Type	Swivel castor with total lock
Wheel diameter	100 mm
Wheel width	35 mm
Tread	solid polyamide wheel, 70±5 Shore D
Wheel centre	polyamide
Bearing	roller bearing
Load capacity, dynamic	200 kg
Load capacity, static	250 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	128 mm
Offset	40 mm
Brake	total lock (locks wheel and swivel)
Weight	0.87 kg
Temperature, continuous	-25 to +80 °C
Temperature, short exposure (max. 10 min)	-30 to +110 °C
Top plate size	70 mm
Tread hardness	70 Shore D

Fork zinc electroplated and Cr(VI)-free.

Properties and use

Low wear, little effort to keep rolling and easy to turn. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.