# Swivel castor with total lock 100 mm, polyamide, plain bearing, bolt hole 12.5 mm, 200 kg, product code 40944

Swivel castor with total lock with a 100 mm wheel, solid polyamide wheel, on plain bearing. It carries 200 kg dynamic and 250 kg static, fixed with a 12.5 mm bolt hole. The total lock brakes the rotation of the wheel and the swivel head.



Drawing number **2-065-20D** | Product code **40944** | EAN **3838461409448**

| | |
|---|---|
| **Type** | Swivel castor with total lock |
| **Wheel diameter** | 100 mm |
| **Wheel width** | 35 mm |
| **Tread** | solid polyamide wheel, 70±5 Shore D |
| **Wheel centre** | polyamide |
| **Bearing** | plain bearing |
| **Load capacity, dynamic** | 200 kg |
| **Load capacity, static** | 250 kg |
| **Fitting** | single bolt hole |
| **Hole diameter** | 12.5 mm |
| **Overall height** | 128 mm |
| **Offset** | 40 mm |
| **Brake** | total lock (locks wheel and swivel) |
| **Weight** | 0.83 kg |
| **Temperature, continuous** | -25 to +80 °C |
| **Temperature, short exposure (max. 10 min)** | -30 to +110 °C |
| **Top plate size** | 70 mm |
| **Tread hardness** | 70 Shore D |

Fork zinc electroplated and Cr(VI)-free.

## Properties and use

Low wear, little effort to keep rolling and easy to turn. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.