# Fixed castor 125 mm, elastic rubber, roller bearing, plate 105x85 mm, 200 kg, product code 41005

Fixed castor, 125 mm wheel diameter, elastic rubber tyre, running on roller bearing. Rated load is 200 kg dynamic, 250 kg static, mounted on a 105x85 mm top plate with hole distance 80x60 mm.



Drawing number **2-071-25V** | Product code **41005** | EAN **3838461410055**

| | |
|---|---|
| **Type** | Fixed castor |
| **Wheel diameter** | 125 mm |
| **Wheel width** | 35 mm |
| **Tread** | elastic rubber tyre, 70 Shore A |
| **Tread colour** | green |
| **Wheel centre** | polyamide |
| **Bearing** | roller bearing |
| **Load capacity, dynamic** | 200 kg |
| **Load capacity, static** | 250 kg |
| **Top plate** | 105x85 mm |
| **Hole distance** | 80x60 mm |
| **Fixing hole diameter** | 9 mm |
| **Overall height** | 155 mm |
| **Weight** | 0.64 kg |
| **Temperature, continuous** | -25 to +80 °C |
| **Temperature, short exposure (max. 10 min)** | -30 to +110 °C |

Fork zinc electroplated and Cr(VI)-free. Tread free of PAH (EU directive 2005/69/EC).

## Properties and use

Rolls with low resistance and is gentle on the floor. Obstacles pass with little effort. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.