
Stainless steel swivel castor 80 mm, polyamide, roller bearing, bolt hole 12.5 mm, 150 kg, product code 41313

Stainless steel swivel castor with a 80 mm wheel, solid polyamide wheel, on roller bearing. It carries 150 kg dynamic and 180 kg static, fixed with a 12.5 mm bolt hole.





Drawing number **2-755 L12** | Product code **41313** | EAN **3838461413131**

Type	Stainless steel swivel castor
Wheel diameter	80 mm
Wheel width	35 mm
Tread	solid polyamide wheel, 70±5 Shore D
Wheel centre	polyamide
Bearing	roller bearing
Load capacity, dynamic	150 kg
Load capacity, static	180 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	106 mm
Offset	34 mm
Weight	0.63 kg
Temperature, continuous	-25 to +80 °C
Temperature, short exposure (max. 10 min)	-30 to +110 °C
Top plate size	73 mm
Tread hardness	70 Shore D

Properties and use

The castor can be washed often and suits hot and wet conditions. Stainless steel does not rust, so it keeps its finish. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.