
# Stainless steel swivel castor with total lock 100 mm, polyamide, roller bearing, bolt hole 12.5 mm, 200 kg, product code 41335

Stainless steel swivel castor with total lock, 100 mm wheel diameter, solid polyamide wheel, running on roller bearing. Rated load is 200 kg dynamic, 250 kg static, fixed with a 12.5 mm bolt hole. The total lock brakes the rotation of the wheel and the swivel head.






Drawing number **2-789 L12** | Product code **41335** | EAN **3838461413353**

| | |
|---|---|
| **Type** | Stainless steel swivel castor with total lock |
| **Wheel diameter** | 100 mm |
| **Wheel width** | 35 mm |
| **Tread** | solid polyamide wheel, 70±5 Shore D |
| **Wheel centre** | polyamide |
| **Bearing** | roller bearing |
| **Load capacity, dynamic** | 200 kg |
| **Load capacity, static** | 250 kg |
| **Fitting** | single bolt hole |
| **Hole diameter** | 12.5 mm |
| **Overall height** | 128 mm |
| **Offset** | 40 mm |
| **Brake** | total lock (locks wheel and swivel) |
| **Weight** | 0.65 kg |
| **Temperature, continuous** | -25 to +80 °C |
| **Temperature, short exposure (max. 10 min)** | -30 to +110 °C |
| **Top plate size** | 73 mm |
| **Tread hardness** | 70 Shore D |

## Properties and use

The castor can be washed often and suits hot and wet conditions. Stainless steel does not rust, so it keeps its finish. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.