
Stainless steel swivel castor 125 mm, grey rubber, roller bearing, bolt hole 12.5 mm, 130 kg, product code 41543

Stainless steel swivel castor with grey rubber tread, wheel diameter 125 mm, on roller bearing. It carries 130 kg dynamic and 160 kg static, fixed with a 12.5 mm bolt hole.





Drawing number **2-967 L12** | Product code **41543** | EAN **3838461415432**

Type	Stainless steel swivel castor
Wheel diameter	125 mm
Wheel width	37 mm
Tread	grey rubber tread, 83 Shore A
Tread colour	grey
Wheel centre	polypropylene
Bearing	roller bearing
Load capacity, dynamic	130 kg
Load capacity, static	160 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	155 mm
Offset	40 mm
Weight	1.15 kg
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C
Top plate size	73 mm

Tread free of PAH (EU directive 2005/69/EC).

Properties and use

The grey rubber protects the floor. The castor suits wet areas and steam cleaning, and low obstacles pass smoothly. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.