Stainless steel swivel castor with total lock 80 mm, grey rubber, plain bearing, bolt hole 12.5 mm, 65 kg, product code 41553

Stainless steel swivel castor with total lock with a 80 mm wheel, grey rubber tread, on plain bearing. It carries 65 kg dynamic and 80 kg static, fixed with a 12.5 mm bolt hole. The total lock brakes the rotation of the wheel and the swivel head.





Drawing number **2-986 L12** | Product code **41553** | EAN **3838461415531**

Type	Stainless steel swivel castor with total lock
Wheel diameter	80 mm
Wheel width	30 mm
Tread	grey rubber tread, 83 Shore A
Tread colour	grey
Wheel centre	polypropylene
Bearing	plain bearing
Load capacity, dynamic	65 kg
Load capacity, static	80 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	106 mm
Offset	40 mm
Brake	total lock (locks wheel and swivel)
Weight	0.73 kg
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C
Top plate size	73 mm

Tread free of PAH (EU directive 2005/69/EC).

Properties and use

The grey rubber protects the floor. The castor suits wet areas and steam cleaning, and low obstacles pass smoothly. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.