
Stainless steel swivel castor 150 mm, polyamide, roller bearing, bolt hole 12.5 mm, 300 kg, product code 41674

Stainless steel swivel castor, 150 mm wheel diameter, solid polyamide wheel, running on roller bearing. Rated load is 300 kg dynamic, 370 kg static, fixed with a 12.5 mm bolt hole.





Drawing number **2-758 L12** | Product code **41674** | EAN **3838461416743**

Type	Stainless steel swivel castor
Wheel diameter	150 mm
Wheel width	46 mm
Tread	solid polyamide wheel, 70±5 Shore D
Wheel centre	polyamide
Bearing	roller bearing
Load capacity, dynamic	300 kg
Load capacity, static	370 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	180 mm
Offset	50 mm
Weight	1.7 kg
Temperature, continuous	-25 to +80 °C
Temperature, short exposure (max. 10 min)	-30 to +110 °C
Top plate size	93 mm
Tread hardness	70 Shore D

Properties and use

The castor can be washed often and suits hot and wet conditions. Stainless steel does not rust, so it keeps its finish. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.