Stainless steel swivel castor 200 mm, polyurethane, plain bearing, bolt hole 12.5 mm, 300 kg, product code 41753

Stainless steel swivel castor with polyurethane tread, wheel diameter 200 mm, on plain bearing. It carries 300 kg dynamic and 370 kg static, fixed with a 12.5 mm bolt hole.





Drawing number **2-054-40D** | Product code **41753** | EAN **3838461417535**

Type	Stainless steel swivel castor
Wheel diameter	200 mm
Wheel width	50 mm
Tread	polyurethane tread, 92 Shore A
Tread colour	green
Wheel centre	polyamide
Bearing	plain bearing
Load capacity, dynamic	300 kg
Load capacity, static	370 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	232 mm
Offset	60 mm
Weight	3.04 kg
Temperature, continuous	-25 to +55 °C
Temperature, short exposure (max. 10 min)	-30 to +55 °C
Top plate size	93 mm
Tread material	Injection-moulded polyurethane

Properties and use

Little deformation when the unit stands still, and oil resistant. The temperature range is wide, see the table. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.