Stainless steel swivel castor with total lock 160 mm, polyurethane, roller bearing, bolt hole 12.5 mm, 300 kg, product code 41754

Stainless steel swivel castor with total lock with a 160 mm wheel, polyurethane tread, on roller bearing. It carries 300 kg dynamic and 370 kg static, fixed with a 12.5 mm bolt hole. The total lock brakes the rotation of the wheel and the swivel head.





Drawing number **2-055-32V** | Product code **41754** | EAN **3838461417542**

Type	Stainless steel swivel castor with total lock
Wheel diameter	160 mm
Wheel width	50 mm
Tread	polyurethane tread, 92 Shore A
Tread colour	green
Wheel centre	polyamide
Bearing	roller bearing
Load capacity, dynamic	300 kg
Load capacity, static	370 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	190 mm
Offset	50 mm
Brake	total lock (locks wheel and swivel)
Weight	1.64 kg
Temperature, continuous	-25 to +55 °C
Temperature, short exposure (max. 10 min)	-30 to +55 °C
Top plate size	93 mm
Tread material	Injection-moulded polyurethane

Properties and use

Little deformation when the unit stands still, and oil resistant. The temperature range is wide, see the table. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.