# Stainless steel swivel castor 200 mm, elastic rubber, plain bearing, bolt hole 12.5 mm, 300 kg, product code 41815

Stainless steel swivel castor, 200 mm wheel diameter, elastic rubber tyre, running on plain bearing. Rated load is 300 kg dynamic, 370 kg static, fixed with a 12.5 mm bolt hole.






Drawing number **2-044-40D** | Product code **41815** | EAN **3838461418150**

| | |
|---|---|
| **Type** | Stainless steel swivel castor |
| **Wheel diameter** | 200 mm |
| **Wheel width** | 50 mm |
| **Tread** | elastic rubber tyre, 70 Shore A |
| **Tread colour** | green |
| **Wheel centre** | polyamide |
| **Bearing** | plain bearing |
| **Load capacity, dynamic** | 300 kg |
| **Load capacity, static** | 370 kg |
| **Fitting** | single bolt hole |
| **Hole diameter** | 12.5 mm |
| **Overall height** | 232 mm |
| **Offset** | 60 mm |
| **Weight** | 3.04 kg |
| **Temperature, continuous** | -25 to +80 °C |
| **Temperature, short exposure (max. 10 min)** | -30 to +110 °C |
| **Top plate size** | 93 mm |

Tread free of PAH (EU directive 2005/69/EC).

## Properties and use

Absorbs shocks and rolls smoothly over bumps. Easy to keep clean. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.