
# Stainless steel swivel castor 150 mm, grey rubber, roller bearing, bolt hole 12.5 mm, 170 kg, product code 41914

Stainless steel swivel castor, 150 mm wheel diameter, grey rubber tread, running on roller bearing. Rated load is 170 kg dynamic, 210 kg static, fixed with a 12.5 mm bolt hole.






Drawing number **2-968 L12** | Product code **41914** | EAN **3838461419140**

| | |
|---|---|
| **Type** | Stainless steel swivel castor |
| **Wheel diameter** | 150 mm |
| **Wheel width** | 40 mm |
| **Tread** | grey rubber tread, 83 Shore A |
| **Tread colour** | grey |
| **Wheel centre** | polypropylene |
| **Bearing** | roller bearing |
| **Load capacity, dynamic** | 170 kg |
| **Load capacity, static** | 210 kg |
| **Fitting** | single bolt hole |
| **Hole diameter** | 12.5 mm |
| **Overall height** | 180 mm |
| **Offset** | 50 mm |
| **Weight** | 1.55 kg |
| **Temperature, continuous** | -20 to +70 °C |
| **Temperature, short exposure (max. 10 min)** | -30 to +80 °C |
| **Top plate size** | 93 mm |

Tread free of PAH (EU directive 2005/69/EC).

## Properties and use

The grey rubber protects the floor. The castor suits wet areas and steam cleaning, and low obstacles pass smoothly. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.