
Stainless steel swivel castor 150 mm, grey rubber, plain bearing, bolt hole 12.5 mm, 170 kg, product code 41915

Stainless steel swivel castor with grey rubber tread, wheel diameter 150 mm, on plain bearing. It carries 170 kg dynamic and 210 kg static, fixed with a 12.5 mm bolt hole.





Drawing number **2-975 L12** | Product code **41915** | EAN **3838461419157**

Type	Stainless steel swivel castor
Wheel diameter	150 mm
Wheel width	40 mm
Tread	grey rubber tread, 83 Shore A
Tread colour	grey
Wheel centre	polypropylene
Bearing	plain bearing
Load capacity, dynamic	170 kg
Load capacity, static	210 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	180 mm
Offset	50 mm
Weight	1.5 kg
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C
Top plate size	93 mm

Tread free of PAH (EU directive 2005/69/EC).

Properties and use

The grey rubber protects the floor. The castor suits wet areas and steam cleaning, and low obstacles pass smoothly. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.