Stainless steel swivel castor 180 mm, grey rubber, roller bearing, bolt hole 12.5 mm, 200 kg, product code 41925

Stainless steel swivel castor with a 180 mm wheel, grey rubber tread, on roller bearing. It carries 200 kg dynamic and 250 kg static, fixed with a 12.5 mm bolt hole.





Drawing number **2-970 L12** | Product code **41925** | EAN **3838461419256**

Type	Stainless steel swivel castor
Wheel diameter	180 mm
Wheel width	50 mm
Tread	grey rubber tread, 83 Shore A
Tread colour	grey
Wheel centre	polypropylene
Bearing	roller bearing
Load capacity, dynamic	200 kg
Load capacity, static	250 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	210 mm
Offset	55 mm
Weight	2.8 kg
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C
Top plate size	93 mm

Tread free of PAH (EU directive 2005/69/EC).

Properties and use

The grey rubber protects the floor. The castor suits wet areas and steam cleaning, and low obstacles pass smoothly. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.