
Stainless steel swivel castor with total lock 200 mm, grey rubber, roller bearing, bolt hole 12.5 mm, 230 kg, product code 41963

Stainless steel swivel castor with total lock with grey rubber tread, wheel diameter 200 mm, on roller bearing. It carries 230 kg dynamic and 280 kg static, fixed with a 12.5 mm bolt hole. The total lock brakes the rotation of the wheel and the swivel head.





Drawing number **2-985 L12** | Product code **41963** | EAN **3838461419638**

Type	Stainless steel swivel castor with total lock
Wheel diameter	200 mm
Wheel width	50 mm
Tread	grey rubber tread, 83 Shore A
Tread colour	grey
Wheel centre	polypropylene
Bearing	roller bearing
Load capacity, dynamic	230 kg
Load capacity, static	280 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	232 mm
Offset	60 mm
Brake	total lock (locks wheel and swivel)
Weight	3.25 kg
Top plate size	93 mm

Fork zinc electroplated and Cr(VI)-free.

Properties and use

The grey rubber protects the floor. The castor suits wet areas and steam cleaning, and low obstacles pass smoothly. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.