Stainless steel swivel castor with total lock 200 mm, elastic rubber, ball bearing, bolt hole 12.5 mm, 300 kg, product code 42284

Stainless steel swivel castor with total lock with elastic rubber tyre, wheel diameter 200 mm, on ball bearing. It carries 300 kg dynamic and 370 kg static, fixed with a 12.5 mm bolt hole. The total lock brakes the rotation of the wheel and the swivel head.





Drawing number **2-045-40K** | Product code **42284** | EAN **3838461422843**

Type	Stainless steel swivel castor with total lock
Wheel diameter	200 mm
Wheel width	50 mm
Tread	elastic rubber tyre, 70 Shore A
Tread colour	green
Wheel centre	polyamide
Bearing	ball bearing
Load capacity, dynamic	300 kg
Load capacity, static	370 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	232 mm
Offset	60 mm
Brake	total lock (locks wheel and swivel)
Weight	3.33 kg
Temperature, continuous	-25 to +80 °C
Temperature, short exposure (max. 10 min)	-30 to +110 °C
Top plate size	93 mm

Tread free of PAH (EU directive 2005/69/EC).

Properties and use

Absorbs shocks and rolls smoothly over bumps. Easy to keep clean. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.