Stainless steel wheel 200 mm, polyurethane, ball bearing, axle hole 20 mm, 500 kg, product code 42295

Stainless steel wheel, 200 mm wheel diameter, polyurethane tread, running on ball bearing. Rated load is 500 kg dynamic, 620 kg static, with a 20 mm axle hole.



Drawing number **2-050-40K** | Product code **42295** | EAN **3838461422959**

Type	Stainless steel wheel
Wheel diameter	200 mm
Wheel width	50 mm
Tread	polyurethane tread, 92 Shore A
Tread colour	green
Wheel centre	polyamide
Bearing	ball bearing
Load capacity, dynamic	500 kg
Load capacity, static	620 kg
Axle hole	20 mm
Weight	1.1 kg
Temperature, continuous	-25 to +55 °C
Temperature, short exposure (max. 10 min)	-30 to +55 °C
Fitting	Wheel hub
Hub length	58 mm
Tread material	Injection-moulded polyurethane

Properties and use

Little deformation when the unit stands still, and oil resistant. The temperature range is wide, see the table. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.