Stainless steel wheel 200 mm, elastic rubber, ball bearing, axle hole 20 mm, 400 kg, product code 42304

Stainless steel wheel, 200 mm wheel diameter, elastic rubber tyre, running on ball bearing. Rated load is 400 kg dynamic, 500 kg static, with a 20 mm axle hole.



Drawing number **2-040-40K** | Product code **42304** | EAN **3838461423048**

Type	Stainless steel wheel
Wheel diameter	200 mm
Wheel width	50 mm
Tread	elastic rubber tyre, 70 Shore A
Tread colour	green
Wheel centre	polyamide
Bearing	ball bearing
Load capacity, dynamic	400 kg
Load capacity, static	500 kg
Axle hole	20 mm
Weight	1.1 kg
Temperature, continuous	-25 to +80 °C
Temperature, short exposure (max. 10 min)	-30 to +110 °C
Fitting	Wheel hub
Hub length	58 mm

Tread free of PAH (EU directive 2005/69/EC).

Properties and use

Absorbs shocks and rolls smoothly over bumps. Easy to keep clean. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.