
Fixed castor 125 mm, black rubber, ball bearing, plate 105x85 mm, 200 kg, Art. 2-111-25K

Fixed castor with black rubber tread, wheel diameter 125 mm, on ball bearing. It carries 200 kg dynamic and 250 kg static, mounted on a 105x85 mm top plate with hole distance 80x60 mm.





Drawing number **2-111-25K** | SKU **42353** | EAN **3838461423536**

Type	Fixed castor
Wheel diameter	125 mm
Wheel width	40 mm
Tread	black rubber tread, 92 Shore A
Tread colour	black
Wheel centre	aluminium
Bearing	ball bearing
Load capacity, dynamic	200 kg
Load capacity, static	250 kg
Top plate	105x85 mm
Hole distance	80x60 mm
Fixing hole diameter	9 mm
Overall height	155 mm
Weight	1.05 kg
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C

Fork zinc electroplated and Cr(VI)-free. Tread free of PAH (EU directive 2005/69/EC).

Properties and use

Moves goods quietly over uneven floors and carries heavy loads. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.