
Swivel castor 125 mm, polyurethane, ball bearing, plate 105x85 mm, 300 kg, product code 42395

Swivel castor with polyurethane tread, wheel diameter 125 mm, on ball bearing. It carries 300 kg dynamic and 370 kg static, mounted on a 105x85 mm top plate with hole distance 80x60 mm.





Drawing number **2-122-25K** | Product code **42395** | EAN **3838461423956**

Type	Swivel castor
Wheel diameter	125 mm
Wheel width	40 mm
Tread	polyurethane tread, 92 Shore A
Tread colour	orange/red/brown
Wheel centre	aluminium
Bearing	ball bearing
Load capacity, dynamic	300 kg
Load capacity, static	370 kg
Top plate	105x85 mm
Hole distance	80x60 mm
Fixing hole diameter	9 mm
Overall height	155 mm
Offset	40 mm
Weight	1.25 kg
Temperature, continuous	-25 to +55 °C
Temperature, short exposure (max. 10 min)	-40 to +55 °C
Tread material	Injection-moulded polyurethane

Fork zinc electroplated and Cr(VI)-free.

Properties and use

Low own weight and chemical resistance. Heavy loads move with little effort. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.