Heavy duty wheel 160 mm, polyurethane, ball bearing, axle hole 20 mm, 850 kg, Art. 2-140-32K

Heavy duty wheel with polyurethane tread, wheel diameter 160 mm, on ball bearing. It carries 850 kg dynamic and 1060 kg static, with a 20 mm axle hole.



Drawing number **2-140-32K** | SKU **42503** | EAN **3838461425035**

Type	Heavy duty wheel
Wheel diameter	160 mm
Wheel width	50 mm
Tread	polyurethane tread, 92 Shore A
Tread colour	orange/red/brown
Wheel centre	cast iron
Bearing	ball bearing
Load capacity, dynamic	850 kg
Load capacity, static	1060 kg
Axle hole	20 mm
Weight	3.05 kg
Temperature, continuous	-25 to +55 °C
Temperature, short exposure (max. 10 min)	-40 to +55 °C
Fitting	Wheel hub
Tread material	Injection-moulded polyurethane

Properties and use

Carries high loads and keeps its shape when the unit stands for a long time. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.