Heavy duty wheel 160 mm, black rubber, ball bearing, axle hole 20 mm, 500 kg, product code 42505

Heavy duty wheel, 160 mm wheel diameter, black rubber tread, running on ball bearing. Rated load is 500 kg dynamic, 620 kg static, with a 20 mm axle hole.



Drawing number **2-130-32K** | Product code **42505** | EAN **3838461425059**

Type	Heavy duty wheel
Wheel diameter	160 mm
Wheel width	50 mm
Tread	black rubber tread, 92 Shore A
Tread colour	black
Wheel centre	cast iron
Bearing	ball bearing
Load capacity, dynamic	500 kg
Load capacity, static	620 kg
Axle hole	20 mm
Weight	3 kg
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C
Fitting	Wheel hub

Tread free of PAH (EU directive 2005/69/EC).

Properties and use

Kind to the floor and passes obstacles with ease. Heavy loads ride softly. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.