
Heavy duty swivel castor with total lock 200 mm, cast iron, ball bearing, plate 140x110 mm, 800 kg, product code 42533

Heavy duty swivel castor with total lock with cast iron tread, wheel diameter 200 mm, on ball bearing. It carries 800 kg dynamic and 1000 kg static, mounted on a 140x110 mm top plate with hole distance 105x80 mm. The total lock brakes the rotation of the wheel and the swivel head.





Drawing number **2-153-40K** | Product code **42533** | EAN **3838461425332**

Type	Heavy duty swivel castor with total lock
Wheel diameter	200 mm
Wheel width	50 mm
Tread	cast iron tread, 180-220 180-220 HB
Wheel centre	cast iron
Bearing	ball bearing
Load capacity, dynamic	800 kg
Load capacity, static	1000 kg
Top plate	140x110 mm
Hole distance	105x80 mm
Fixing hole diameter	11 mm
Overall height	240 mm
Offset	60 mm
Brake	total lock (locks wheel and swivel)
Directional lock	optional
Weight	6.9 kg
Temperature, continuous	-40 to +130 °C
Temperature, short exposure (max. 10 min)	-40 to +130 °C

Fork zinc electroplated and Cr(VI)-free.

Properties and use

Wears slowly and rolls with low resistance. Large temperature changes are no problem. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.