
Fixed castor 100 mm, black rubber, ball bearing, plate 105x85 mm, 170 kg, Art. 2-111-20K

Fixed castor, 100 mm wheel diameter, black rubber tread, running on ball bearing. Rated load is 170 kg dynamic, 210 kg static, mounted on a 105x85 mm top plate with hole distance 80x60 mm.





Drawing number **2-111-20K** | SKU **42544** | EAN **3838461425448**

Type	Fixed castor
Wheel diameter	100 mm
Wheel width	40 mm
Tread	black rubber tread, 92 Shore A
Tread colour	black
Wheel centre	aluminium
Bearing	ball bearing
Load capacity, dynamic	170 kg
Load capacity, static	210 kg
Top plate	105x85 mm
Hole distance	80x60 mm
Fixing hole diameter	9 mm
Overall height	128 mm
Weight	1 kg
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C

Fork zinc electroplated and Cr(VI)-free. Tread free of PAH (EU directive 2005/69/EC).

Properties and use

Moves goods quietly over uneven floors and carries heavy loads. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.