
Heavy duty swivel castor with total lock 200 mm, polyamide, plain bearing, plate 140x110 mm, 500 kg, product code 42573, wheel centre white

Heavy duty swivel castor with total lock with a 200 mm wheel, solid polyamide wheel, on plain bearing. It carries 500 kg dynamic and 620 kg static, mounted on a 140x110 mm top plate with hole distance 105x80 mm. The total lock brakes the rotation of the wheel and the swivel head.





Drawing number **2-063-40D** | Product code **42573** | EAN **3838461425738**

Type	Heavy duty swivel castor with total lock
Wheel diameter	200 mm
Wheel width	50 mm
Tread	solid polyamide wheel, 70±5 Shore D
Wheel centre	polyamide
Bearing	plain bearing
Load capacity, dynamic	500 kg
Load capacity, static	620 kg
Top plate	140x110 mm
Hole distance	105x80 mm
Fixing hole diameter	11 mm
Overall height	240 mm
Offset	60 mm
Brake	total lock (locks wheel and swivel)
Directional lock	optional
Weight	3.05 kg
Temperature, continuous	-25 to +80 °C
Temperature, short exposure (max. 10 min)	-30 to +110 °C
Tread hardness	70 Shore D

Fork zinc electroplated and Cr(VI)-free.

Properties and use

Low wear, little effort to keep rolling and easy to turn. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.