# Wheel 125 mm, polypropylene, ball bearing, axle hole 12 mm, 150 kg, product code 42765

Wheel with a 125 mm wheel, solid polypropylene wheel, on ball bearing. It carries 150 kg dynamic and 180 kg static, with a 12 mm axle hole.



Drawing number **2-682-25K** | Product code **42765** | EAN **3838461427657**

| | |
|---|---|
| **Type** | Wheel |
| **Wheel diameter** | 125 mm |
| **Wheel width** | 38 mm |
| **Tread** | solid polypropylene wheel, 60±5 Shore D |
| **Wheel centre** | polypropylene |
| **Bearing** | ball bearing |
| **Load capacity, dynamic** | 150 kg |
| **Load capacity, static** | 180 kg |
| **Axle hole** | 12 mm |
| **Weight** | 0.31 kg |
| **Temperature, continuous** | -20 to +60 °C |
| **Fitting** | Wheel hub |
| **Tread hardness** | 60 Shore D |

## Properties and use

Polypropylene resists acids, wears slowly and rolls with low resistance. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.