Heavy duty wheel 250 mm, black rubber, ball bearing, axle hole 20 mm, 500 kg, Art. 2-110-50K

Heavy duty wheel, 250 mm wheel diameter, black rubber tread, running on ball bearing. Rated load is 500 kg dynamic, 700 kg static, with a 20 mm axle hole.



Drawing number **2-110-50K** | SKU **43504** | EAN **3838461435041**

Type	Heavy duty wheel
Wheel diameter	250 mm
Wheel width	50 mm
Tread	black rubber tread, 65 Shore A
Tread colour	black
Wheel centre	aluminium
Bearing	ball bearing
Load capacity, dynamic	500 kg
Load capacity, static	700 kg
Axle hole	20 mm
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C
Fitting	Wheel hub
Hub length	60 mm

Tread free of PAH (EU directive 2005/69/EC).

Properties and use

Moves goods quietly over uneven floors and carries heavy loads. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.