Heavy duty swivel castor with total lock 250 mm, black rubber, ball bearing, plate 135x110 mm, 550 kg, Art. 2-113-50K

Heavy duty swivel castor with total lock, 250 mm wheel diameter, black rubber tread, running on ball bearing. Rated load is 500 kg dynamic, 670 kg static, mounted on a 135x110 mm top plate with hole distance 105x80 mm. The total lock brakes the rotation of the wheel and the swivel head.



Drawing number **2-113-50K** | SKU **43840** | EAN **3838461438400**

Type	Heavy duty swivel castor with total lock
Wheel diameter	250 mm
Wheel width	50 mm
Tread	black rubber tread, 65 Shore A
Tread colour	black
Wheel centre	aluminium
Bearing	ball bearing
Load capacity, dynamic	500 kg
Load capacity, static	670 kg
Top plate	135x110 mm
Hole distance	105x80 mm
Fixing hole diameter	11 mm
Overall height	289 mm
Brake	total lock (locks wheel and swivel)
Directional lock	optional
Temperature, continuous	-20 to +70 °C
Temperature, short exposure (max. 10 min)	-30 to +80 °C
Load capacity at 4 km/h	550 kg

Fork zinc electroplated and Cr(VI)-free. Tread free of PAH (EU directive 2005/69/EC).

Properties and use

Moves goods quietly over uneven floors and carries heavy loads. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.