
Swivel castor 100 mm, polypropylene, ball bearing, bolt hole 12.5 mm, 125 kg, product code 44038, wheel centre white

Swivel castor, 100 mm wheel diameter, solid polypropylene wheel, running on ball bearing. Rated load is 125 kg dynamic, 150 kg static, fixed with a 12.5 mm bolt hole.





Drawing number **2-766-20K** | Product code **44038** | EAN **3838461440380**

Type	Swivel castor
Wheel diameter	100 mm
Wheel width	35 mm
Tread	solid polypropylene wheel, 60±5 Shore D
Wheel centre	polypropylene
Bearing	ball bearing
Load capacity, dynamic	125 kg
Load capacity, static	150 kg
Fitting	single bolt hole
Hole diameter	12.5 mm
Overall height	128 mm
Offset	40 mm
Weight	0.68 kg
Temperature, continuous	-20 to +60 °C
Top plate size	70 mm
Tread hardness	60 Shore D

Fork zinc electroplated and Cr(VI)-free.

Properties and use

Polypropylene resists acids, wears slowly and rolls with low resistance. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.