Institutional swivel castor 125 mm, polypropylene, ball bearing, bolt hole 12 mm, 100 kg, product code 44809

Institutional swivel castor, 125 mm wheel diameter, solid polypropylene wheel, running on ball bearing. Rated load is 100 kg dynamic, 120 kg static, fixed with a 12 mm bolt hole.





Drawing number **2-817** | Product code **44809** | EAN **3838461448096**

Type	Institutional swivel castor
Wheel diameter	125 mm
Wheel width	32 mm
Tread	solid polypropylene wheel, 60±5 Shore D
Tread colour	grey
Wheel centre	polypropylene
Bearing	ball bearing
Load capacity, dynamic	100 kg
Load capacity, static	120 kg
Fitting	single bolt hole
Hole diameter	12 mm
Overall height	155 mm
Offset	38 mm
Weight	0.85 kg
Temperature, continuous	-20 to +60 °C
Top plate size	61 mm
Tread hardness	60 Shore D

Fork zinc electroplated and Cr(VI)-free.

Properties and use

Dust-proof and leaves no trail on the floor. Turns easily. On request: other wheel and tyre colours, and an electrically conductive or antistatic tyre (ESD).

Send us the drawing or the dimensions of the castor you are replacing and we confirm the match. Quote within 1 to 2 working days.

Specifications from the LIV product database, October 2026.